SYSTEM AND METHOD FOR PROVIDING CONFIGURATION DATA SUCH AS FOR CONFIGURING ELECTRONIC MAIL ACCESS

Related Application

[0001]   This application is based upon prior filed provisional application Serial No. 60/493,624 filed August 8, 2003.

Field of the Invention

[0002]   This invention relates generally to the field of obtaining configuration data, such as for electronic mailboxes, and this invention relates to accessing automatically different electronic mail accounts using configuration information from a user system.

Background of the Invention

[0003]   As electronic mail (email) increases in popularity, it has become the norm for a user to maintain several separate mailboxes to help manage their email. Typically, the user will have a mailbox dedicated to corporate email and another mailbox dedicated to personal email. Some users have additional mailboxes. For example, these additional email addresses are used when registering for services on the Internet.

[0004]   Managing multiple mailboxes can be challenging because the user has to check periodically

each mailbox for new email. Services such as Yahoo™ now provide mailbox services that automatically poll a predefined list of mailboxes to determine if new email has been received. New emails that have been received in any of the polled mailboxes are retrieved into the requesting mailbox. As a result, the user only has to check the requesting mailbox to determine if new email has arrived in any of the other mailboxes. This reduces the number of mailboxes that are required to be checked periodically. Other services allow a user to access their mailboxes through a plurality of devices such as, but not limited to, mobile phones, mobile computing devices, for example, personal digital assistants (POA's) and other communications devices.

[0005] Each of the separate mailboxes has a unique set of configuration parameters, such as a mailbox server name or a mailbox server address. Additionally, as part of these configuration parameters, each of the mailboxes may be implemented in one of a variety of mailbox protocols, such as Post Office Protocol (POP) or Internet Message Access Protocol (IMAP), giving rise to differing sets of configuration parameters for each of the mailboxes. Typically, the user would have to determine these configuration parameters for each of the mailboxes and configure manually a web service associated with a web server to access each of the mailboxes.

[0006] One proposal in U.S. patent application publication no. 2002/0174194 provides a single web-based interface that gives the user access to a plurality of different message accounts on different message servers. This proposal allows email clients to access only a subset, namely messaging, of an IMAP server, and requires a user to establish all

configuration parameters for the IMAP server
functionality.   Other similar proposals requiring a
user to determine and manually configure a web service
for configuration parameters are disclosed in U.S.
Patent No. 5,968,117 and U.S. published patent
application no. 2002/0112007, where message sources are
established during setup and a technical support can be
called.   U.S. Patent No. 6,446,114 discloses the use of
an agent that searches a user database to determine a
list of messaging systems the user subscribes.   The
agent recalls from an application database any
procedures for accessing the messaging systems and logs
onto each messaging system to retrieve new messages.

Summary of the Invention

[0007]   The present invention is advantageous and now
provides a system, method and computer-readable medium
that uses a configuration module that can provide
configuration data for a requesting web service and act
as a pass-through service.   The web service, for
example, could be a new internet service provider (ISP)
that uses configuration data for accessing electronic
mail from another internet service provider.   The
mailbox could be a gateway window into another
electronic mailbox and use configuration data on-the-
fly.   The module could automatically configure access
to electronic mail from a plurality of different
electronic mailboxes.

[0008]   In one aspect of the present invention, a
user system includes a plurality of different email
clients, each with different configuration data for
accessing respective electronic mailboxes that are
different from each other.   A configuration module
retrieves the configuration data required for accessing

the different electronic mailboxes of a user. The configuration module is operative for generating data objects for each electronic mailbox relating to the configuration data. The configuration module also submits each data object as a distributed object module to a web service. The web service can be configured as a pass-through or configured to access the respective electronic mailboxes associated with each data object.

[0009] In one aspect of the present invention, a web service interface module formats the data objects as distributed object modules for submission to a web service. The web browser or email client accesses the web service or a targeted electronic mailbox. The user system can include a personal computer or mobile communications device.

[0010] In another aspect of the present invention, the configuration module is implemented as a component object module that could be an ActiveX control. In yet another aspect of the present invention, the data objects are formatted within the configuration module using an extensible mark-up language (XML) for transmission to an XML-compliant web service. The user system could include a plurality of user computing sources. The electronic mailboxes to be accessed could reside on an internet or intranet server. A method is also set forth and a computer-readable medium that includes a plurality of import modules, data objects and a web service interface module.

Brief Description of the Drawings

[0011] Other objects, features and advantages of the present invention will become apparent from the detailed description of the invention which follows,

when considered in light of the accompanying drawings in which:

[0012]   FIG. 1 is a block diagram of a system for providing configuring data to a web service, such as configuring for electronic mail access, according to one aspect of the present invention.

[0013]   FIG. 2 is a block diagram of the configuration engine that can be used with the system shown in FIG. 1.

[0014]   FIG. 3 is a flowchart illustrating a method of retrieving and formatting configuration data objects according to one aspect of the present invention.

[0015]   FIG. 4 is a schematic block diagram illustrating an exemplary mobile wireless communications device for use in the present invention.

Detailed Description of the Preferred Embodiments

[0016]   The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout, and prime notation is used to indicate similar elements in alternative embodiments.

[0017]   FIG. 1 is a block diagram of an electronic mail system **10**, as one non-limiting example of the present invention, that permits configuration of different mailboxes and allows configuration for automatic access of different email accounts. It

should be understood that the present invention provides a system and method that provides configuration data for a web service that could be used as a pass-through service or used for configuring a web service or other agent for electronic mail access. In one aspect of the invention, a source of configuration data could be a user system and the configuration module retrieves the configuration data from a user system typically at the request of a web service. This configuration module could be operative for generating data objects related to the configuration data and submitting each data object as a distributed object module to a web service. The configuration data could be data used for accessing an electronic mailbox. The web service could be a new internet service provide (ISP) that uses configuration data for accessing electronic mail from another or previous internet service provider. The mailbox could be a gateway window into another electronic mailbox and the gateway window could use configuration data on-the-fly.

[0018]   The web service interface module could format data objects as distributed object modules for submission to a web service. The user system could be a web browser or e-mail client. A user operates with the system from his user system **12,** such as a home or work computer, or wireless, mobile communications device such as a hand-held Blackberry unit, as one non-limiting example. The user system could be a plurality of systems. The user is able to access a plurality of source mailboxes **20** using at least one of a plurality of email clients **22, 24,** and **26.** A web service **30** as part of a web server **30a** allows the user to access the source mailboxes **20** through the web service **30,** or from one or more target mailboxes **32.** The web service **30** or

the target mailboxes **32** may be accessed using a variety of methods known to those skilled in the art. In example embodiments, the web service **30** and the target mailboxes **32** may be accessed using a web browser, an email client, or another application configured to access the web service **32** or the target mailbox **30**. The web browser, mail client or other application for accessing the web service **30** or target mailboxes **32** may be resident on a variety of systems that could include, but are not limited to, personal computers and mobile communications devices. Although the system of the present invention will be described in relation to its use with a personal computer, the system of the present invention could be used with a mobile phone, personal digital assistant (PDA), or other communications device.

[0019] It should be understood that the use of the term web services **30** is broad and can also refer to the many application services on web servers used by those skilled in the art. Web services usually include a combination of programming and data, which are typically available from a web server for web users or the use of other web-connected programs as provided by an application service provider. Typically, web services use an extensible mark-up language (XML) as a standard for formatting data to be communicated. Any type of arrangement can be used to access the web service, including a peer-to-peer arrangement, a central server, or other architecture and communications. Middleware could also be used. Data formats can be standardized and data exchanged using the Extensive Mark-up Language (XML), which is also the foundation for the Web Services Description Language (WSDL). Different web servers could be used, including

the open source Apache or Microsoft's Internet
Information Server (IIS). Other web services could
include Novel's web server for users of its netware
operating system or the IBM family of Lotus domino
servers, for example, for IMB's OS/390 and AS/400
customers. Naturally, any web server should be able to
download requests for File Transfer Protocol (FTP)
files in a preferred embodiment.

[0020] The target mailbox **32** or the web service **30**
requires complete configuration data **40** for each of the
source mailboxes **20** in order to help the user access
these mailboxes **20**. The configuration data **40** may
include mailbox server name, access port, password,
username, incoming mail server, outgoing mail (SMTP)
server, mail server type, such as IMAP, and other
configuration parameters that may be required to
configure user access to one or more of the source
mailboxes **20**.

[0021] It should be understood that email providers
are free to use any convention they choose for
configuration parameters. For example, many email
providers may use a "defacto standard" convention for
configuration parameters, such as using a mail host
name of "mail.<MailDomain>", where <MailDomain>
represents the provider's e-mail domain (i.e.,
"foo.com"). Another example could be an address, such
as JohnSmith@earthlink.net. The user, of course, may
only know their email address and a password, for
example, "password." Information not known to the
normal user would be POP3 server: pop.earthlink.net,
the SMTP server: smtpauth.earthlink.net, the domain of
earthlink.net, a different user name as indicated
above, the FTP server ftp-www.earthlink.net, an access
ID and DNS address, for example, 207.69.188.XXX, or the

outgoing mail (SMTP) server, and mail server type, such as IMAP.

[0022]   A user is required to provide any email configuration data 40 to the web service 30 or to a unified target mailbox 32. According to one aspect of the present invention, a configuration engine 50 as a software module automatically retrieves the configuration data 40 for one or more of the source mailboxes 20 from at least one of the email clients 22, 24, and 26. The configuration engine 50 transmits some or all of the configuration data 40 to the web service 30 allowing the web service 30 or the target mailboxes 32 to be configured to access one or more of the source mailboxes 20 without requiring the user to provide the configuration data 40.

[0023]   In an example embodiment for the present invention, a number of the source mailboxes 20 reside on servers within a corporate intranet 20a while other source mailboxes 20 reside within servers on the Internet 20b. As will be apparent to those skilled in the art, the mailboxes may be accessed using a variety of protocols such as POP, IMAP or a proprietary mail protocol such as that used in the Microsoft™ Exchange™ server.

[0024]   The user accesses the source mailboxes 20 using one of a plurality of email clients 22, 24, and 26 that are configured in the user system 12 to access the source mailboxes 20. Each email client 22 can access one or more of the source mailboxes 20. Mailbox configuration data 40 that is specific to a respective email client 22, 24, and 26, and the mail protocol used to access the source mailboxes 20, is associated with each respective email client 22, 24, and 26. The email clients 22, 24, and 26 and the configuration data 40

reside on the user system **12**. In other embodiments, the email clients **22, 24,** and **26** and the respective configuration data **40** could reside on a plurality of user systems and not just one system as shown, for example, by the second user system **12a**. In some embodiments, the user system **12** may be any one of a variety of computing devices such as a personal computer, or a mobile computing or communications device, including a PDA or mobile phone.

[0025] FIG. 2 is a block diagram of one example of the configuration engine **50** that retrieves mailbox configuration data **40**. The configuration engine **50**, in one aspect of the present invention, includes an import module **52** having one or more import agents **52, 56,** and **58** that retrieve configuration data **40**. The configuration engine **50** also includes configuration data objects **60** formed of one or more mail protocol specific objects **62, 64,** and **66** and a web service interface **70** for formatting the configuration data objects **60** for the web service **30**.

[0026] Each import agent **52, 56, 58** in the import module **52** is designed to retrieve respective configuration data **40** from a specific type of email client and generate one or more configuration data objects **60**. The configuration data **40** related to a respective email client may reside in various locations. The respective import agent **54, 56,** and **58** retrieves any configuration data **40** from the location specific to each email client **22, 24,** and **26**. In a non-limiting example, the import agent **54** is designed to retrieve configuration data from the Microsoft™ Outlook™ email client **22**. Import agent **56** is designed to retrieve configuration data **40** from the Microsoft™ Outlook Express™ **24** email client. In other example

10

embodiments, import agents can be designed to retrieve configuration data from other types of email clients such as, but not limited to, Eudora and Netscape email clients. In further example embodiments, an import agent may use a Messaging Application Programming Interface (MAPI) to retrieve configuration data **40** for a MAPI-compliant email client. MAPI provides an application programming interface (API) to ensure system independence for messaging applications. A layer of functionality could be provided between applications and any underlying messaging systems and act as messaging middleware. MAPI-compliant applications would communicate through a MAPI subsystem to MAPI service providers that perform requested actions for clients and pass data back through a MAPI system to a MAPI client.

[0027] Also, in a non-limiting embodiment, the configuration data **40** could reside in the configuration registry of the user system **12**. In other example embodiments, the data may reside in email client specific configuration stores.

[0028] The configuration data objects **60** generated by the import module **52** would vary based on the protocol used to access the source mailboxes **20** for which a mail client **22, 24,** and **26** is configured. In an example embodiment, the Microsoft Outlook Express mail client **24** can access source mailboxes **20** that use the Post Office Protocol (POP) or Internet Mail Access Protocol (IMAP). POP, of course, is the internet mail server protocol that provides incoming message storage. The more recent protocol is POP3. POP is operative with the Simple Mail Transfer Protocol (SMTP). Any mail server must run both protocols if it is to receive, store and forward messages. The SMTP protocol

exchanges messages from one mail server to another and
hands messages to the required POP server for an email
mailbox. A POP server can receive a message and hold
it until another POP server is available. The IMAP
version 4 also uses the SMTP transport mechanism, but
it is a more flexible protocol because IMAP allows
users to store mail on a mail server without
downloading all new messages to a local machine.
Internet mail servers, of course, run SMTP in either
POP or IMAP and receive incoming messages from any
source without identity checking. Thus, mail can be
selectively downloaded and read, message headers
reviewed, hierarchical message stores built, address
books supported, and documents linked, authenticated
and searched.

[0029]   In this example, the configuration data
objects **60** generated by the Outlook Express Import
Agent **56** can be POP objects **62** or IMAP objects **64**, for
example. In other embodiments, configuration data
objects **66** could be generated for source mailboxes **20**
that use proprietary mail access protocols. As is
obvious to those skilled in the art, a variety of mail
access protocols exist and configuration data objects
60 could be created for some or all of these mail
access protocols.

[0030]   The web service interface **70** formats the
configuration data objects **60** generated by the import
module **52** for submission to the web service **30**. As is
obvious to one skilled in the art, there are a variety
of formats for submitting data to the web service **30**.
In one non-limiting example, Extensible Mark-up
Language (XML) can be used to format the data for
submission to an XML-compliant web service **30**. The web

service **30** can also be a Simple Object Access Protocol (SOAP) compliant service.

[0031]   XML, of course, as an extensible mark-up language, is a subset of the standard generalized mark-up language (SGML) and allows data to be stored and published on websites and richer in presentation. Custom tags can be created to define the content of documents. Common information formats can be created and the format and data shared on the internet, corporate intranets, and/or other networks. The mark-up symbols in XML are unlimited and self-defining. The channel definition format (CDF) can describe any channel and a specific CDF file can contain data that specifies an initial web page and how frequently it is updated.

[0032]   SOAP allows one program running in one kind of operating system to communicate with the program in the same or another type of operating system by using the HTTP and XML for information exchange. For example, SOAP could specify how to encode an HTTP header and an XML file, thus, allowing one computer to call a program in another computer and pass data, and while also dictating how it can return a response. SOAP is advantageous to allow data to pass through firewall servers that screen-out requests other than those for known applications through a designated port. SOAP is an XML-based protocol that has at least three parts, including (a) an envelope to define a framework for describing what is in a message, (b) a set of encoding rules for expressing application-defined data types, and (c) a convention for representing remote procedure calls and responses. For example, data can be formatted using XML for submission to a web service **30** that is SOAP compliant. For purposes of this

description, the end of this detailed description sets forth an example of data formatted using XML for submission to a SOAP compliant web service. In other embodiments, the web service **30** may require a proprietary format for data submission, and the web service interface **70** will format the configuration data **40** in the proprietary format.

[0033]   The configuration engine **50** is preferably implemented using a series of instructions for execution on a computing device. In one example embodiment, the configuration engine **50** is implemented as an ActiveX control. ActiveX is operative as a Component Object Model (COM) and provides the framework for building software components that communicate with each other. Distributed COM (DCOM) allows different ActiveX components to communicate across networks, such as the internet. ActiveX controls can be automatically downloaded and executed by a web browser. Distributed object applications can be built in active web pages, and ActiveX controls can be downloaded to different browsers and clients. ActiveX controls can be held in a web browser as a container and distributed over the internet or corporate intranets. ActiveX controls can also manage and update web content and client systems and work closely with a user interface of a targeted operating system. It should be understood that Java Applets or similar component objects could also be used instead of ActiveX controls. It should also be understood that other object models can be used in accordance with the present invention, as well as other scripting languages. It is also possible that object linking and embedding custom controls could be used. Of course, it should be understood for purposes of the present invention that

an object model control could also be any type of
dynamic link library (DLL) module that runs in a
container as an application program uses a component
object model program interface.

[0034]   In the example embodiment, a user accesses a
web browser to access a configuration web page provided
by the web service **30**. The user may request that the
configuration engine **50** be downloaded and executed,
thereby automatically retrieving configuration data **40**
to configure the web service **30** to access source
mailboxes **20** through the target mailbox **32** or through
the web service **30**. In other example embodiments, the
configuration engine **50** may be implemented using Java
and Java Applets. The example embodiments are not
meant to limit the scope of the invention. As is
obvious to those skilled in the art, there are numerous
ways in which the configuration engine may be
implemented.

[0035]   FIG. 3 is a flowchart illustrating an example
of a non-limiting method of automatically configuring
the web service **30** to access source mailboxes **20**
through the target mailbox **32** or the web service **30**.
At step **100**, the user requests that the target mailbox
32 or web service **30** be configured to access one or
more of the source mailboxes **20**. In another non-
limiting example, the configuration engine **50** is
implemented as an ActiveX control that is downloaded
and executed on the user system **12**. At step **102**, the
import module **52** of the configuration engine **50**
retrieves configuration data **40** for the source
mailboxes **20** from the user system **12** and generates
configuration data objects **60**. At step **104**, the web
service interface **70** of the configuration engine **50**
formats the configuration data objects **60** for

submission to the web service **30**. At step **106,** the formatted configuration data is submitted to the web service **30**.

[0036] An example of data formatted using XML for submitting to a SOAP compliant web service **30** is now set forth.

```
<?xml version="1.0" ?>
<IMPORTCONTENT>
 <EMAILCONFIG>

  <POPMAIL>
  <LeaveMail>true</LeaveMail>
  <UseSPA>false</UseSPA>
  <UserId>johndoe1</UserId>
  <Port>110</Port>
  <TimeOut>60</TimeOut>
  <IsSecure>false</IsSecure>
  <SkipAccount>true</SkipAccount>
  <Server>pop.mailserver.net</Server>
  <EmailId>johndoe1@mailserver.net</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 1</DisplayName>
  </POPMAIL>

  <POPMAIL>
  <LeaveMail>true</LeaveMail>
  <UseSPA>false</UseSPA>
  <UserId>JohnDoe2@mailworld.net</UserId>
  <Port>111</Port>
  <TimeOut>60</TimeOut>
  <IsSecure>true</IsSecure>
  <SkipAccount>true</SkipAccount>
  <Server>ipostoffice.mailworld.net</Server>
  <EmailId>JohnDoe2@mailworld.net</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 2</DisplayName>
  </POPMAIL>

  <POPMAIL>
  <LeaveMail>true</LeaveMail>
  <UseSPA>true</UseSPA>
  <UserId>JohnDoe3</UserId>
  <Port>110</Port>
  <TimeOut>60</TimeOut>
  <IsSecure>false</IsSecure>
  <SkipAccount>false</SkipAccount>
```

```
  <Server>pop3.email.msn.com</Server>
  <EmailId>johndoe3@msn.com</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 3</DisplayName>
</POPMAIL>

<POPMAIL>
  <LeaveMail>true</LeaveMail>
  <UseSPA>true</UseSPA>
  <UserId>555555,5555</UserId>
  <Port>110</Port>
  <TimeOut>60</TimeOut>
  <IsSecure>false</IsSecure>
  <SkipAccount>true</SkipAccount>
  <Server>pop.compuserve.com</Server>
  <EmailId>johndoe4@somehere.com</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 4</DisplayName>
</POPMAIL>

<WEBMAIL>
  <UserId>blair</UserId>

<Server>http://exchange.123office.com/exchange/johndoe5
</Server>
  <EmailId>johndoe5@123office.com</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 5</DisplayName>
  </WEBMAIL>

<WEBMAIL>
  <UserId>johndoe6@msn.com</UserId>
  <Server>http://oe.msn.msnmail.hotmail.com/cgi-
bin/hmdata</Server>
  <EmailId>johndoe6@msn.com</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 6</DisplayName>
  </WEBMAIL>

<WEBMAIL>
  <UserId>johndoe7@hotmail.com</UserId>

<Server>http://services.msn.com/svcs/hotmail/httpmail.a
sp</Server>
  <EmailId>johndoe7@him.com</EmailId>
  <Password>testpassword</Password>
  <DisplayName>John Doe 7</DisplayName>
  </WEBMAIL>

<IMAP>
  <UserId>johndoe8</UserId>
```

```
<Port>110</Port>
<TimeOut>60</TimeOut>
<IsSecure>false</IsSecure>
<SkipAccount>true</SkipAccount>
<Server>imap.cs.com</Server>
<EmailId>johndoe8@cs.com</EmailId>
<Password>testpassword</Password>
<DisplayName>John Doe 8</DisplayName>
</IMAP>

<IMAP>
<UserId>johndoe9@corporation.com</UserId>
<Port>10001</Port>
<TimeOut>120</TimeOut>
<IsSecure>false</IsSecure>
<SkipAccount>true</SkipAccount>
<Server>imap.corporation.com</Server>
<EmailId>johndoe9@corporation.com</EmailId>
<Password>testpassword</Password>
<DisplayName>John Doe 9</DisplayName>
</IMAP>

</EMAILCONFIG>
</IMPORTCONTENT>
```

[0037] An exemplary hand-held mobile wireless communications device **1000** that can be used in the present invention is further described in the example below with reference to FIG. 4. The device **1000** includes a housing **1200**, a keyboard **1400** and an output device **1600**. The output device shown is a display **1600**, which is preferably a full graphic LCD. Other types of output devices may alternatively be utilized. A processing device **1800** is contained within the housing **1200** and is coupled between the keyboard **1400** and the display **1600**. The processing device **1800** controls the operation of the display **1600**, as well as the overall operation of the mobile device **1000**, in response to actuation of keys on the keyboard **1400** by the user.

[0038] The housing **1200** may be elongated vertically, or may take on other sizes and shapes (including

clamshell housing structures). The keyboard may include a mode selection key, or other hardware or software for switching between text entry and telephony entry.

[0039]   In addition to the processing device **1800**, other parts of the mobile device **1000** are shown schematically in FIG. 4. These include a communications subsystem **1001**; a short-range communications subsystem **1020**; the keyboard **1400** and the display **1600**, along with other input/output devices **1060**, **1080**, **1100** and **1120**; as well as memory devices **1160**, **1180** and various other device subsystems **1201**. The mobile device **1000** is preferably a two-way RF communications device having voice and data communications capabilities. In addition, the mobile device **1000** preferably has the capability to communicate with other computer systems via the Internet.

[0040]   Operating system software executed by the processing device **1800** is preferably stored in a persistent store, such as the flash memory **1160**, but may be stored in other types of memory devices, such as a read only memory (ROM) or similar storage element. In addition, system software, specific device applications, or parts thereof, may be temporarily loaded into a volatile store, such as the random access memory (RAM) **1180**. Communications signals received by the mobile device may also be stored in the RAM **1180**.

[0041]   The processing device **1800**, in addition to its operating system functions, enables execution of software applications **1300A-1300N** on the device **1000**. A predetermined set of applications that control basic device operations, such as data and voice communications **1300A** and **1300B**, may be installed on the

19

device **1000** during manufacture. In addition, a
personal information manager (PIM) application may be
installed during manufacture. The PIM is preferably
capable of organizing and managing data items, such as
e-mail, calendar events, voice mails, appointments, and
task items. The PIM application is also preferably
capable of sending and receiving data items via a
wireless network **1401**. Preferably, the PIM data items
are seamlessly integrated, synchronized and updated via
the wireless network **1401** with the device user's
corresponding data items stored or associated with a
host computer system.   Communication functions,
including data and voice communications, are performed
through the communications subsystem **1001**, and possibly
through the short-range communications subsystem. The
communications subsystem **1001** includes a receiver **1500**,
a transmitter **1520**, and one or more antennas **1540** and
1560. In addition, the communications subsystem **1001**
also includes a processing module, such as a digital
signal processor (DSP) **1580**, and local oscillators
(LOs) **1601**. The specific design and implementation of
the communications subsystem **1001** is dependent upon the
communications network in which the mobile device **1000**
is intended to operate. For example, a mobile device
1000 may include a communications subsystem **1001**
designed to operate with the Mobitex™, Data TAC™ or
General Packet Radio Service (GPRS) mobile data
communications networks, and also designed to operate
with any of a variety of voice communications networks,
such as AMPS, TDMA, CDMA, PCS, GSM, etc. Other types
of data and voice networks, both separate and
integrated, may also be utilized with the mobile device
1000.

[0042] Network access requirements vary depending upon the type of communication system. For example, in the Mobitex and DataTAC networks, mobile devices are registered on the network using a unique personal identification number or PIN associated with each device. In GPRS networks, however, network access is associated with a subscriber or user of a device. A GPRS device therefore requires a subscriber identity module, commonly referred to as a SIM card, in order to operate on a GPRS network.

[0043] When required network registration or activation procedures have been completed, the mobile device **1000** may send and receive communications signals over the communication network **1401**. Signals received from the communications network **1401** by the antenna **1540** are routed to the receiver **1500,** which provides for signal amplification, frequency down conversion, filtering, channel selection, etc., and may also provide analog to digital conversion. Analog-to-digital conversion of the received signal allows the DSP **1580** to perform more complex communications functions, such as demodulation and decoding. In a similar manner, signals to be transmitted to the network **1401** are processed (e.g. modulated and encoded) by the DSP **1580** and are then provided to the transmitter **1520** for digital to analog conversion, frequency up conversion, filtering, amplification and transmission to the communication network **1401** (or networks) via the antenna **1560**.

[0044] In addition to processing communications signals, the DSP **1580** provides for control of the receiver **1500** and the transmitter **1520**. For example, gains applied to communications signals in the receiver **1500** and transmitter **1520** may be adaptively controlled

through automatic gain control algorithms implemented in the DSP **1580**.

[0045] In a data communications mode, a received signal, such as a text message or web page download, is processed by the communications subsystem **1001** and is input to the processing device **1800**. The received signal is then further processed by the processing device **1800** for an output to the display **1600**, or alternatively to some other auxiliary I/O device **1060**. A device user may also compose data items, such as e-mail messages, using the keyboard **1400** and/or some other auxiliary I/O device **1060**, such as a touchpad, a rocker switch, a thumb-wheel, or some other type of input device. The composed data items may then be transmitted over the communications network **1401** via the communications subsystem **1001**.

[0046] In a voice communications mode, overall operation of the device is substantially similar to the data communications mode, except that received signals are output to a speaker **1100**, and signals for transmission are generated by a microphone **1120**. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, may also be implemented on the device **1000**. In addition, the display **1600** may also be utilized in voice communications mode, for example to display the identity of a calling party, the duration of a voice call, or other voice call related information.

[0047] The short-range communications subsystem enables communication between the mobile device **1000** and other proximate systems or devices, which need not necessarily be similar devices. For example, the short-range communications subsystem may include an infrared device and associated circuits and components,

22

or a Bluetooth™ communications module to provide for communication with similarly-enabled systems and devices.

[0048] It will be appreciated that the above description relates to preferred embodiments by way of example only. Many variations on the systems and methods described above will be obvious to those knowledgeable in the field, and such obvious variations are within the scope of the invention as described and claimed, whether or not expressly described. For example, automatic configuration systems and methods according to aspects of the invention may be applied to other types of data systems than mail systems and other mail clients, access protocols and data formats other than those specifically described above and shown in the drawings.

[0049] Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.